



**NOTES:**

1. INLET: CO2 FITTING WITH CGA 320 NUT
2. OUTLETS: 5/16" BARB SHUTOFF WITH CHECK
3. GAUGES: 30#, 2000#
4. SAFETY BLOW-OFF: 60 ±5 PSI W/PULL RING
5. WORKING PRESSURE: 0-50 PSI
6. BONNET: BLACK WITH T-HANDLE

MATERIAL	NAME	DATE
	DRAWN LG	04/07/15
FINISH	ENG APPR.	P.F. 04/07/15
	<b>PROPRIETARY AND CONFIDENTIAL</b>	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2" BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE:  
**REG, PRI, BEER, 30#, TANK FTG, 5/16B-CV SHUTOFF, 2000#, SFTY PULL RING, T-HNDL**

SIZE	DWG. NO.	REV
<b>A</b>	<b>3741-BR-30MT_SALES</b>	<b>A</b>

SCALE: 1:4	DO NOT SCALE DRAWING	<b>SHEET 1 OF 1</b>
------------	----------------------	---------------------