



NOTES:

1. INLET: CO2 FITTING WITH CGA 320 NUT
2. OUTLET: 1/4" FLARE WITH CHECK
3. GAUGES: 160# AND 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. POLY BONNET WITH RED ADJ CAP

MATERIAL	NAME	DATE
	DRAWN	JPK 05/04/10
FINISH	ENG APPR.	P.F. 06/14/10
	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		



TITLE: **REG, PRI, SODA, 160#,
TNK FTG, 1/4F-CV OUT,
2000#, POLY, RED**

SIZE	DWG. NO.	REV
A	T5741PMHP_SALES	C
SCALE: 1:2	DO NOT SCALE DRAWING	SHEET 1 OF 1