



6' HP HOSE



CO2 TANK FTG WITH CGA 320 NUT



**NOTES:**

1. INLET: 1/4" FLARE
2. OUTLETS: 1/4" FLARE WITH CHECK (2 EA)
3. GAUGES: 160#, 100#, 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, BLUE CAPS
7. UL252: SERIES 5740

MATERIAL	DRAWN	NAME	DATE
	JRS	JRS	11/12/10
FINISH	ENG APPR.		
	<b>PROPRIETARY AND CONFIDENTIAL</b>		
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005			
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.			



TITLE:  
**REG PR SOD WM, 2P2P, 160/100, BLU 1/4F IN/OUT, 2K, 6' HP W/CGA320**

SIZE	DWG. NO.	REV
<b>A</b>	<b>T8861-6B_SALES</b>	<b>C</b>

SCALE: 1:1      DO NOT SCALE DRAWING      SHEET 1 OF 1