

NOTES:

- 1. INLET: CO2 TANK FITTING WITH NUT
- 2. OUTLET: 5/16" BARB SHUTOFF WITH CHECK
- 3. GAUGES: NONE
- 4. SAFETY BLOW-OFF: 60 ± 5 PSI
- 5. OPERATING PRESSURE: 30-45 PSI
- 6. BONNET: ZINC, BLACK

| | PROPRIETARY | | |
|----------|-------------|------|----------|
| FINISH | ENG APPR. | | |
| | DRAWN | JPK | 08/02/11 |
| MATERIAL | | NAME | DATE |

DIMENSIONS ARE IN INCHES

TOLERANCES:
FRACTIONAL ± 1/64
ANGULAR: MACH ± 1/2*
BEND ±
TWO PLACE DECIMAL ± 0.015
THREE PLACE DECIMAL ± 0.005

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.



REG, FLOW CTRL, NO GAGES, TNK FTG, 5/16B-CV SHUTOFF, BLACK, 30-45 PSI

SIZE DWG. NO. REV A

SCALE: 1:2

DO NOT SCALE DRAWING

SHEET 1 OF 1