



## NOTES

1. INLET/THRU: 5/16" BARB
2. OUTLETS: 5/16" BARB W/ SHUT-OFFS
3. GAUGES: 60#
4. SAFETY BLOW-OFF: 60 ± 5 PSI.
5. WORKING PRESSURE: 0-50 PSI
6. BONNETS: POLY, GOLD

MATERIAL	DRAWN	08/19/09	 <small>3248 NORTHWESTERN DR. SAN ANTONIO, TX 78238</small>
	FINISH	ENG APPR.	
DIMENSIONS ARE IN INCHES	<b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		TITLE:
TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± ° BEND ± ° TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005			<b>REG SEC BEER, 6P6P, 60#,          5/16B IN/THRU, 5/16B          SHUTOFF, POLY GOLD</b>
	<b>A</b> DWG. NO. T1696ST-2N_SALES -		SCALE: 1:1
	DO NOT SCALE DRAWING		<b>SHEET 1 OF 1</b>