


NOTES:

1. INLET: CO2 FITTING WITH CGA 320 NUT
2. OUTLETS: 1/4" FLARE
3. GAUGES: 160# AND 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, BLACK
7. UL252: SERIES 5740

MATERIAL	NAME	DATE	 <small>2348 NORTHWESTERN DR SAN ANTONIO TX 78238</small>	
	DRAWN	EG		06/08/10
FINISH	ENG APPR.	PF	TITLE:	
	<p align="center">PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.</p>		<p>REG. PRI SODA, 160#, TNK FTG, 1/4F-CV OUT, 2000#, POLY BLK</p>	
DIMENSIONS ARE IN INCHES	TOLERANCES:		SIZE DWG. NO.	REV
	FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		A T5741PMHPBK_SALES	A
			SCALE: 1:1	DO NOT SCALE DRAWING
			SHEET 1 OF 1	